



[IPN Home](#) | [Search](#) | [Order](#) | [Shopping Cart](#) | [Login](#) | [Site Map](#) | [Help](#)

Patent Plaques



JP56002848A: EXHAUST GAS CLEANING CATALYST AND ITS MANUFACTURE

[View Images \(1 pages\)](#)

Country: JP Japan

Inventor(s): FUJITANI YOSHIYASU
MURAKI HIDEAKI
KONDO SHIRO
YOKOTA KOJI
TOMITA MAKOTO
SOFUGAWA HIDEO

BEST AVAILABLE COPY

Applicant(s): TOYOTA CENTRAL RES & DEV LAB INC



[News, Profiles, Stocks and More about this company](#)

Issued/Filed Dates: Jan. 13, 1981 / June 20, 1979

Application Number: JP1979000078593

IPC Class: B01J 023/40; B01J 023/64; B01J 023/89; B01D 053/36; B01D 053/36; B01J 021/10;

Abstract: **Purpose:** To manufacture a catalyst for cleaning NOx, CO, etc., present in the exhaust gas, having a highly efficient cleaning capability, at low cost by depositing platinum, palladium, etc., on a porous sintered body consisting of magnesia, alumina, iron oxide, etc., as a carrier.

Constitution: A mixture of alumina-magnesia spinel (MgAl_2O_4), Al_2O_3 , and MgO , together with any one or both of iron oxide and manganese oxide, or cerium oxide, etc., in which the amount of Al_2O_3 and MgO is 25wt% or less on the basis of the spinel, is molded into a desired shape and then heated to obtain a porous sintered body. Then, the sintered body as a carrier is deposited with a catalyst component composed of any one or both of platinum and palladium in order to manufacture a cleaning catalyst capable of removing hydrocarbons, NOx, CO, etc., present in the exhaust gas from an internal combustion engine, etc., having excellent high-temperature strength and durability, at low cost.

COPYRIGHT: (C)1981,JPO&Japio

Foreign References: n ne

(No patents reference this one)